

PTFE MESH 4/4

PTFE MESH4/4 is a 4 x 4 mm

OPEN MESH, PTFE-coated glass fabric designed for use as conveyor belting.


PTFE MESH4/4 is used in

drying and curing ovens across a range of industries.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
Weight:	g/m ²	430	FTMS 191A-5041
Thickness:	mm	0.890	FTMS 191A-5030
Tensile Strength:	N/cm	550 x 550	FTMS 191A-5102
Mesh Size:	mm	4 x 4	-
Open Area:	%	75	-
PTFE Content:	%	27	-
Temperature Resistance:	°C	-150 to +260	-
Standard Widths:	mm	2700, 3200*	-

*The fabrication of a conveyor belt from the above product requires the fabric to be cut and squared. This will involve a reduction in width, and thus the exact minimum width can only be confirmed on receipt of any enquiry with belt dimensions.

TECHPLAS UK



MESH4/4

Techplas UK Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes, Cheshire, WA8 ORZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:

carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.