


# PTFE GLASSCLOTH

**PTFE GLASSCLOTH RGA103 S** is a Premium Grade PTFE-coated fabric with a high performance, silicone pressure-sensitive adhesive on one side. The product has a yellow corrugated liner to protect the adhesive surface and to ease identification and use.

**PTFE GLASSCLOTH RGA103 S** is used extensively in the packaging industry for heat sealing and wrapping applications and for tool and mould release linings.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
<b>Base Thickness:</b>	mm	0.075	FTMS 191A-5030
<b>Adhesive Thickness:</b>	mm	0.045	FTMS 191A-5030
<b>Base PTFE-Fabric weight:</b>	g/m <sup>2</sup>	155	FTMS 191A-5041
<b>180° Peel Adhesion Strength:</b>	N/cm	5.2	ASTM D3330-83
<b>Tensile Strength:</b>	N/cm	180 x 140	FTMS 191A-5102
<b>Adhesive Type:</b>	-	Silicone	-
<b>Temperature Resistance:</b>	°C	-73 to +260	-
<b>Standard Widths:</b>	mm	1000	-

**TECHPLAS UK**



## RGA103 S

**Techplas UK** Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes,  
Cheshire, WA8 ORZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:

carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.