


PTFE GLASSCLOTH

PTFE GLASSCLOTH RGP105 is a PTFE-coated fibreglass based on a single glasscloth. It possesses an extra smooth and glossy surface.

PTFE GLASSCLOTH RGP105 is typically used as a liner in baking sheet applications and as a release in packaging applications.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
Weight:	g/m ²	270	FTMS 191A-5041
Thickness:	mm	0.125	FTMS 191A-5030
Tensile Strength:	N/cm	300 x 290	FTMS 191A-5102
Trap Tear Strength:	N	15 x 13	FTMS 191A-5136
PTFE Content:	%	61	-
Temperature Resistance:	°C	-150 to +260	-
Standard Widths:	mm	1020	-

TECHPLAS UK



RGP105

Techplas UK Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes,
Cheshire, WA8 0RZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:
carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.