


PTFE GLASSCLOTH

PTFE GLASSCLOTH RGP205 is a Primary-Series PTFE-coated glass cloth with excellent release and chemical resistance properties, even at elevated temperatures.

PTFE GLASSCLOTH RGP205 is typically used for “non-stick” applications in the packaging and plastics industries, and also as release sheets for food and other processing industries.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
Weight:	g/m ²	250	FTMS 191A-5041
Thickness:	mm	0.120	FTMS 191A-5030
Tensile Strength:	N/cm	290 x 260	FTMS 191A-5102
Trap Tear Strength:	N	20 x 18	FTMS 191A-5136
PTFE Content:	%	58	-
Temperature Resistance:	°C	-150 to +260	-
Standard Widths:	mm	1000; 1250; 1525	



RGP205

Techplas UK Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes,
Cheshire, WA8 0RZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:
carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.