


# PTFE GLASSCLOTH

**PTFE GLASSCLOTH RGP206 AS** is a standard grade PTFE-coated fibreglass fabric with an anti-static coating. It has excellent mechanical strength and a slightly textured surface.

**PTFE GLASSCLOTH RGP206 AS** is used as a release sheet in the packaging industries where Static dissipative properties are required.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
<b>Weight:</b>	g/m <sup>2</sup>	300	FTMS 191A-5030
<b>Thickness:</b>	mm	0.140	FTMS 191A-5030
<b>Tensile Strength:</b>	N/cm	300 x 260	FTMS 191A-5102
<b>Trap Tear Strength:</b>	N	20 x 18	FTMS 191A-5136
<b>Surface Resistivity:</b>	Ω/ Square	<1 x 10 <sup>6</sup>	ASTM D257-78
<b>PTFE Content:</b>	%	65	-
<b>Temperature Resistance:</b>	°C	-150 to +260	-
<b>Standard Widths:</b>	mm	1000	-

TECHPLAS UK



## RGP206 AS

**Techplas UK** Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes,  
Cheshire, WA8 ORZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:

carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.