


# PTFE GLASSCLOTH

**PTFE GLASSCLOTH RGP210-2** is a standard grade PTFE coated woven glass fabric on plied thread. It provides good release properties and chemical and wear characteristics over wide temperature ranges.

**PTFE GLASSCLOTH RGP210-2** – Typical applications are in the packaging industry, release sheets for press lamination, food processing, composite release sheets for aerospace industry, electrical insulation, belting and gasketing.

TYPICAL PROPERTIES	UNIT	VALUE	TEST METHOD
<b>Weight:</b>	g/m <sup>2</sup>	500	FTMS 191A-5041
<b>Thickness:</b>	mm	0.235	FTMS 191A-5030
<b>Tensile Strength:</b>	N/cm	540 x 500	FTMS 191A-5102
<b>Trap Tear Strength:</b>	N	38 x 38	FTMS 191A-5136
<b>PTFE Content:</b>	%	60	-
<b>Temperature Resistance:</b>	°C	-150 to +260	-
<b>Standard Widths:</b>	mm	1000, 1525, 2000, 2600	-

**TECHPLAS UK**



## RGP210-2

**Techplas UK** Performance Plastics sales, fabrication and distribution are situated at:

1 Tanhouse Lane, Widnes,  
Cheshire, WA8 ORZ

Tel: +44 (01925) 604812

Fax: +44 (01925) 602449

Email:

carolecatterall@aol.com

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. Techplas UK assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. Techplas UK warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.